## Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Previously Presented) A device comprising at least two containers configured in such a manner as to be superposable on a stacking axis, one of the containers comprising a lid with a hinge, the other container being added on said lid, each container defining a housing, and at least one of the housings containing an applicator member secured to the housing.
- 2. (Previously Presented) A device according to claim 1, wherein the device is configured in such a manner that the housings can be opened independently of one another.
- 3. (Original) A device according to claim 1, wherein each container comprises a closure lid.
- 4. (Original) A device according to claim 3, wherein with the exception of a top lid, each lid is secured to the container that is immediately above it when the containers are superposed and when the stacking axis is vertical.
- 5. (Previously Presented) A device according to claim 1, wherein at least one of the housings is closed in a sealed manner when the containers are superposed.
- 6. (Original) A device according to claim 1, wherein the hinge may enable one of the containers to be pivoted relative to the other, at least partially, about an axis of rotation that is not parallel to the stacking axis.
- 7. (Original) A device according to claim 1, further comprising at least two hinges.
- 8. (Original) A device according to claim 7, wherein the hinges are angularly offset around the stacking axis of the containers.

- 9. (Original) A device according to claim 1, wherein at least one of the housings contains a cosmetic or a care product.
  - 10. (Canceled)
- 11. (Original) A device according to claim 1, further comprising at least one means for fixing one container to a container immediately below it.
- 12. (Original) A device according to claim 11, wherein said fixing means comprises screwing, snap-fastening or friction on at least one of a receptacle and a closure cap of a receptacle.
- 13. (Original) A device according to claim 1, wherein the device does not comprise fixing means for fixing by snap-fastening, screwing, or by friction on a receptacle.
- 14. (Currently Amended) A <u>device according to claim 1, configured to close a</u> receptacle. <u>closure cap for closing a receptacle, comprising a device as defined in claim 1.</u>
  - 15. (Original) A receptacle fitted with a device as defined in claim 1.
- in such a manner as to be superposable on a stacking axis, and at least two hinges, each hinge enabling one of the containers to be pivoted relative to another container, at least partially, about an axis of rotation that is not parallel to the stacking axis, each container defining a housing, at least two of the housings containing different substances, the hinges being angularly offset around the stacking axis of the containers, the axis of rotation of the hinges being not parallel to each other. other,

wherein at least a first one of the at least three containers comprises a lid connected via at least one of the at least two hinges to the first container, and wherein a second one of the at least three containers is fixed on the lid.

17. (Original) A device according to claim 16, the device being configured in such a manner that the housings can be opened independently of one another.

18. (Canceled)

- 19. (Original) A device according to claim 16, wherein one of the containers is configured so as to form a closure lid for closing the other container.
- 20. (Original) A device according to claim 16, wherein each container comprises a closure lid.
- 21. (Original) A device according to claim 20, wherein, with the exception of a top lid, each lid is secured to the container that is immediately above it when the containers are superposed and when the stacking axis is vertical.
- 22. (Currently Amended) A device according to claim 19, wherein, with the exception of a bottom container, each wherein at least one container serves as a closure lid for the container that is immediately beneath it when the containers are superposed and when the stacking axis is vertical.
- 23. (Original) A device according to claim 16, wherein at least one of the housings is closed in a sealed manner when the containers are superposed.

## 24-25. (Canceled)

- 26. (Original) A device according to claim 16, wherein at least one of the housings contains a cosmetic or a care product.
- 27. (Original) A device according to claim 16, wherein at least one of the housings comprises an applicator member.
- 28. (Original) A device according to claim 16, further comprising a means for fixing one container to a container immediately below it
- 29. (Original) A device according to claim 28, wherein said fixing means comprises screwing, snap-fastening, or friction on a receptacle or on a closure cap of a receptacle.

- 30. (Original) A device according to claim 16, wherein the device does not comprise fixing means for fixing by snap-fastening, screwing, or by friction on a receptacle.
- 31. (Currently Amended) A <u>device according to claim 16</u>, configured to close a <u>receptacle</u>. closure cap for closing a receptacle comprising a device as defined in claim 16.
- 32. (Currently Amended) A <u>eap-device</u> according to claim 31, further comprising a bottom portion configured so as to be fixed on a receptacle and so as to enable the device to be removably fixed thereto, one of the containers comprising a lid with a hinge, the other container being added on said lid.
  - 33. (Original) A receptacle fitted with a device as defined in claim 15.
- 34. (Currently Amended) A device comprising at least three containers configured in such a manner so as to be superposable on a stacking axis, and at least two hinges, each hinge enabling one of the containers to be pivoted relative to the other(s), at least partially, about an axis of rotation that is not parallel to the stacking axis, each container defining a housing, each container, with the exception of a bottom container, serving as a closure lid for the container that is immediately beneath it when the containers are superposed and when the stacking axis is vertical, the hinges being angularly offset around the stacking axis of the containers, the axis of rotation of the hinges being not parallel to each other, other,

wherein at least one hinge is a film hinge made by integrally molding a plastic material with at least one of the containers.

- 35. (Original) A device according to claim 34, the device being configured in such a manner that the housings can be opened independently of one another.
- 36. (Original) A device according to claim 34, wherein one of the containers comprises a lid connected via the hinge to said container, and wherein the other container is fixed on said lid.

37. (Original) A device according to claim 34, wherein at least one of the housings is closed in a sealed manner when the containers are superposed.

38-39. (Canceled)

A ...

- 40. (Original) A device according to claim 34, wherein at least one of the housings contains a substance.
- 41. (Original) A device according to claim 40, wherein the substance is a cosmetic or a care product.
- 42. (Original) A device according to claim 34, wherein at least one of the housings comprises an applicator member.
- 43. (Original) A device according to claim 34, further comprising means for fixing one container to a container immediately below it.
- 44. (Original) A device according to claim 41, wherein said fixing means comprises screwing, snap-fastening, or friction on a receptacle or on a closure cap of a receptacle.
- 45. (Original) A device according to claim 34, wherein the device does not comprise fixing means for fixing by snap-fastening, screwing, or friction on a receptacle.
- 46. (Currently Amended) A <u>device according to claim 34, configured to close a receptacle.</u> closure cap for closing a receptacle, the cap comprising a device as defined in claim 34.
- 47. (Currently Amended) A <u>eap device</u> according to claim 46, comprising a bottom portion configured so as to be fixed on a receptacle and so as to enable a device to be removably fixed thereto, said device comprising at least two containers configured in such a manner as to be superposable on a stacking axis, and at least one hinge interconnecting the two containers and enabling one of the containers to be pivoted relative to the other(s), at least partially, about an axis of rotation that is not parallel to the stacking axis, each container

defining a housing, at least two of the housings containing different substances, wherein one of the containers is configured so as to form a closure lid for closing the other container.

- 48. (Original) A receptacle fitted with a device as defined in claim 34.
- 49. (Currently Amended) A device comprising at least three containers configured in such a manner so as to be superposable on a stacking axis, and at least two hinges, each hinge enabling one of the containers to be pivoted relative to another container, at least partially, about an axis of rotation that is not parallel to the stacking axis, each container defining a housing, at least one of the containers being fixed in a removable manner on the container immediately beneath it, the hinges being angularly offset around the stacking axis of the containers, the axis of rotation of the hinges being not parallel to each-other. other,

wherein at least two consecutive containers comprise grip tabs which are diametrically opposite a hinge and which are positioned side by side when the at least two corresponding containers are stacked.

- 50. (Original) A device according to claim 49, the device being configured in such a manner that the housings can be opened independently of one another.
- 51. (Original) A device according to claim 49, wherein one of the containers comprises a lid connected via the hinge to said container, and wherein the other container is fixed on said lid.
- 52. (Original) A device according to claim 49, wherein one of the containers is configured so as to form a closure lid for closing the other container.
- 53. (Original) A device according to claim 49, wherein each container comprises a closure lid.
- 54. (Original) A device according to claim 53, wherein, with the exception of a top lid, each lid is secured to the container that is immediately above it when the containers are superposed and when the stacking axis is vertical.

kay . . i

- 55. (Currently Amended) A device according to claim 52, wherein, with the exception of a bottom container, each wherein at least one container serves as a closure lid for the container that is immediately beneath it when the containers are superposed and when the stacking axis is vertical.
- 56. (Original) A device according to claim 49, wherein at least one of the housings is closed in a sealed manner when the containers are superposed.
  - 57-58. (Canceled)
- 59. (Original) A device according to claim 49, wherein at least one of the housings contains a substance.
- 60. (Original) A device according to claim 59, wherein the substance is a cosmetic or a care product.
- 61. (Original) A device according to claim 49, wherein at least one of the housings comprises an applicator member.
- 62. (Original) A device according to claim 49, further comprising means for fixing one container to a container immediately below it.
- 63. (Original) A device according to claim 62, wherein said fixing means comprises screwing, snap-fastening, or friction on a receptacle or on a closure cap of a receptacle.
- 64. (Original) A device according to claim 49, wherein the device does not comprise fixing means for fixing by snap-fastening, screwing, or friction on a receptacle.
- 65. (Currently Amended) A <u>device according to claim 49</u>, <u>configured to close a receptacle</u>. <u>elosure cap for closing a receptacle</u>, the <u>cap comprising a device as defined in elaim 49</u>.
- 66. (Currently Amended) A <u>eap-device</u> according to claim 65, further comprising a bottom portion configured so as to be fixed on a receptacle and so as to enable a device to be removably fixed thereto, said receptacle fitted with said device, said device comprising at

least two containers configured in such a manner as to be superposable on a stacking axis, and at least one hinge interconnecting the two containers and enabling one of the containers to be pivoted relative to the other(s), at least partially, about an axis of rotation that is not parallel to the stacking axis, each container defining a housing, at least two of the housings containing different substances,

- 67. (Original) A receptacle fitted with a device as defined in claim 49.
- 68. (Previously Presented) A device comprising at least three containers configured in such a manner as to be superposable on a stacking axis, and at least one hinge enabling one of the containers to be pivoted relative to the other(s), at least partially, about an axis of rotation that is not parallel to the stacking axis, each container defining a housing, at least the housing defined by an end container containing an applicator member secured to the housing, at least one of the containers being fixed in a removable manner on the container immediately beneath it.
- 69. (Original) A device according to claim 68, the device being configured in such a manner that the housings can be opened independently of one another.
- 70. (Original) A device according to claim 68, wherein one of the containers comprises a lid connected via the hinge to said container, and wherein the other container is fixed on said lid.
- 71. (Original) A device according to claim 68, wherein one of the containers is configured so as to form a closure lid for closing the other container.
- 72. (Original) A device according to claim 68, wherein each container comprises a closure lid.
- 73. (Original) A device according to claim 72, wherein, with the exception of a top lid, each lid is secured to the container that is immediately above it when the containers are superposed and when the stacking axis is vertical.

x 11 /2 1 1 1 2 1 2 2 1

- 74. (Original) A device according to claim 71, wherein, with the exception of a bottom container, each container serves as a closure lid for the container that is immediately beneath it when the containers are superposed and when the stacking axis is vertical.
- 75. (Original) A device according to claim 68, wherein at least one of the housings is closed in a sealed manner when the containers are superposed.
  - 76. (Original) A device according to claim 68, comprising at least two hinges.
- 77. (Original) A device according to claim 76, wherein the hinges are angularly offset around the stacking axis of the containers.
- 78. (Previously Presented) A device according to claim 68, wherein at least one of the housings contains a cosmetic or a care product.
- 79. (Original) A device according to claim 68, comprising means for fixing one container to a container immediately below it.
- 80. (Original) A device according to claim 79, wherein said fixing means comprises screwing, snap-fastening, or friction on a receptacle or on a closure cap of a receptacle.
- 81. (Original) A device according to claim 68, the device does not comprise fixing means for fixing by snap-fastening, screwing, or friction on a receptacle.
- 82. (Currently Amended) A <u>device according to claim 68, configured to close a receptacle.</u> elosure cap for closing a receptacle, the cap comprising a device as defined in elaim 68.
- 83. (Currently Amended) A <u>eap-device</u> according to claim 82, comprising a bottom portion configured so as to be fixed on a receptacle and so as to enable the device to be removably fixed thereto.
  - 84. (Original) A receptacle fitted with a device as defined in claim 68.
  - 85. (Previously Presented) A receptacle comprising:a receptacle body; and

a closure cap configured to be removably fixed to the receptacle body, the closure cap comprising:

Karl . with

at least two containers each containing a product or an applicator member, and configured in such a manner as to be superposable on a stacking axis; and

at least one hinge enabling one of the containers to be pivoted relative to the other(s), at least partially, about an axis of rotation that is not parallel to the stacking axis, each container defining a housing, the receptacle body being of a different shape than the containers.

- 86. (Original) A receptacle according to claim 85, wherein the cap comprises at least three containers.
- 87. (Original) A receptacle according to claim 85, wherein at least one of the containers is fixed in a removable manner on the container immediately beneath it.
- 88. (Original) A receptacle according to claim 85, the device being configured in such a manner that the housings can be opened independently of one another.
- 89. (Original) A receptacle according to claim 85, wherein one of the containers comprises a lid connected via the hinge to said container, and wherein the other container is fixed on said lid.
- 90. (Original) A receptacle according to claim 85, wherein one of the containers is configured so as to form a closure lid for closing the other container.
- 91. (Original) A receptacle according to claim 85, wherein each container comprises a closure lid.
- 92. (Original) A receptacle according to claim 91, wherein, with the exception of the top lid, each lid is secured to the container that is immediately above it when the containers are superposed and when the stacking axis is vertical.

and the

- 93. (Original) A receptacle according to claim 90, wherein, with the exception of the bottom container, each container serves as a closure lid for the container that is immediately beneath it when the containers are superposed and when the stacking axis is vertical.
- 94. (Original) A receptacle according to claim 85, wherein at least one of the housings is closed in a sealed manner when the containers are superposed.
  - 95. (Original) A receptacle according to claim 85, comprising at least two hinges.
- 96. (Previously Presented) A receptacle according to claim 95, wherein the hinges are angularly offset around the stacking axis of the containers.
- 97. (Original) A receptacle according to claim 85, wherein at least one of the housings contains at least one cosmetic and/or care product.
- 98. (Original) A receptacle according to claim 85, wherein at least one of the housings comprises an applicator member.
- 99. (Previously Presented) A receptacle according to claim 85, wherein the closure cap is configured to be screwed on the receptacle body.
- 100. (New) A receptacle according to claim 16, wherein at least two of the housings contain different substances.
- 101. (New) A receptacle according to claim 34, wherein each container, with the exception of the bottom container, serves as a closure lid for the container that is immediately beneath it when the containers are superposed and when the stacking axis is vertical.
- 102. (New) A receptacle according to claim 49, wherein at least one of the containers is fixed in a removable manner on the container immediately beneath it.